

Enlarge Your Imagination!

VE-3204 **E**

- 3.2m Eco-Solvent Printer
- Epson I3200 Printhead (4EA)
- 100m Roll Take-Up System
- Semi-cartridge Ink Tank System

 **Max. 135m²/hr**

 **4 Color**

 **3.2m**



Technical Specification

*Quality_A/B mode is used for solid image printing.

Print Speed	135 m ² /hr	65 m ² /hr	45 m ² /hr	35 m ² /hr	25 m ² /hr	12 m ² /hr
Print Resolution	360x1,200 2Pass	720x1,200 / 4Pass	720x1,800 / 6Pass	720x2,400 / 8Pass	720x2,400 / 8Pass	720x2,400 / 8Pass
Reference Mode	Normal				Quality_A	Quality_B
Max Print Width	3,200 mm					
Max Media Width	3,200 mm					
Max Media Load	Diameter : 200 mm / Weight : 70 kg					
Print Mode	Bi-Direction / Uni-Direction					
Printhead	EPSON I3200 – 4ea					
Color	4 Color (K, C, M, Y)					
Ink	G123 DGI Original Eco Solvent Ink					
Interface	TCP / IP					
Environmental Range	Temperature : 16~28 °C Humidity : 35~65% Environmental condition may affect on final printing quality.					
Electricity Requirements	Printer : Single phase 220~240V (50~60 Hz), 8.5A Dryer : Single phase 220~240V (50~60 Hz), 30A					

※ All specifications are subject to change without prior notice.

Dimension for Installation

	Uncrated				Crated			
	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
Printer	4,665	1,002	1,960	850	4,815	1,120	1,750	950

